

Locking Devices, Twist-Lock®, Male Inlet, Reversed Service, Industrial Grade, 30A 125V, 2-Pole 3-Wire Grounding, L5-30R, Gray

By Hubbell Wiring Device-Kellems
Catalog # [HBL2615SWR](#)

Locking Devices, Twist-Lock®, Male Inlet, Reversed Service, Industrial Grade, 30A 125V, 2-Pole 3-Wire Grounding, L5-30R, Gray

Features

- UL type 4X environmental seal while in use and when closed
- High impact, thermoplastic housing for heavy-duty industrial environments
- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
- Catalog number and color coded voltage rating are visible even when in use

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - V0 per UL94 or CSA 22.2 No.0.17, Environmental - Moisture Resistance - Type 4, 4X, 12, IP66 suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Watertight
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L5-30P
Industry Standard(s)	UL Listed, CSA Certified To Type 4, 4X And Type 12

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	30 A
-----------------	------



Voltage Rating Description	125 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	125 VAC
Connectivity	Back Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	30 A

Dimensions

Length	3.75 in
Height	2.69 in
Width	3.75 in
Dimensions	3.75 in x 3.75 in x 2.69 in

General

Specifications	• Blades - Brass • Housing - PBT • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)
UPC	783585458083
Type	Flanged Inlet
Item Type	30A Watertight Safety-Shroud® Reverse Service Flanged Inlet

Logistics

Carton Quantity	5
-----------------	---

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)