

30 Amp, 125, 250 Volts and 277 Volts AC, 2 Pole, 3 Wire, Grounding



30A 125V
NEMA L5-30R
2 HP

30A 250V
NEMA L6-30R
2 HP

30A 277V AC
NEMA L7-30R
3 HP



Plugs

Watertight Safety-Shroud®

IP66 SUITABILITY

UL Type 4X, 12

Description	Cord Dia.	Catalog Number		
Black Valox® housing, white Valox clamps.	.360"-.930" (9-24)	HBL2613SW	HBL2623SW	—
Reverse service, black Valox housing, white Valox clamps (use with HBL2615SWR) (not shown).	.360"-.930" (9-24)	HBL2613SR	—	—

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.360"-.930" (9-24)	HBL2613	HBL2623	HBL2633
Black and white nylon, spring termination.	.360"-.930" (9-24)	HBL2613ST	HBL2623ST	—
Spring termination, all black.	.360"-.930" (9-24)	HBL2613STBK	HBL2623STBK	—
Heat stabilized, gray nylon, 220° F (104° C).	.360"-.930" (9-24)	HBL2613F	HBL2623F	—
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	HBL26CM13	HBL26CM23	—
All black nylon.	.360"-.930" (9-24)	HBL2613BK	HBL2623BK	—

Note: See page C-53 for accessories.

Valise®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Yellow nylon.	.590"-.930" (15.0-23.6)	HBL2613VY	HBL2623VY	—
Corrosion resistant, yellow nylon.	.590"-.930" (15.0-23.6)	HBL26CM13V	—	—
Black nylon.	.590"-.930" (15.0-23.6)	HBL2613VBK	HBL2623VBK	—
Cord clamps with removable inserts. All black nylon.	.360"-.930" (9-24)	—	HBL2623EBK	—

Note: See page C-53 for accessories.

Receptacles

Watertight Safety-Shroud®

IP66 SUITABILITY

UL Type 4X, 12

Description	Catalog Number		
Gray Valox housing and flange, back wired.	HBL2610SW	HBL2620SW	—

Note: See page C-54 for accessories.

Safety-Shroud® Twist-Lock®

IP20 SUITABILITY

Description	Catalog Number		
Gray Valox angle housing, one gang, back wired.	HBL2610AR	HBL2620AR	—
Gray Valox surface mounting, one gang, back wired.	HBL2610SR	HBL2620SR	—
Gray Valox semi-flush, two gang, back wired.	HBL2610SR2	HBL2620SR2	—

Single Flush Receptacles

IP20 SUITABILITY

Description	Catalog Number		
Black nylon face, back and side wired.	HBL2610	HBL2620	HBL2630
Black nylon face, spring terminals.	HBL2610ST	HBL2620ST	—
Blue nylon face, back and side wired.	HBL2610M6	HBL2620M6	—
Isolated ground, orange nylon face, back and side wired.	IG2610	IG2620	—
Isolated ground, orange nylon face, spring termination.	IG2610ST	IG2620ST	—
Corrosion resistant, yellow nylon face, back and side wired.	HBL26CM10	HBL26CM20	—
Ring terminal connection.	HBL2610RT	HBL2620RT	—


Note: See page C-52 for accessories.

Insulgrip® Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	HBL2616	HBL2626	HBL2636
Nylon casing, back wire, spring termination.	HBL2616ST	HBL2626ST	—
Heat stabilized, gray nylon, 220° F (104° C).	HBL2616F	HBL2626F	—

Note: See page C-52 for accessories.

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.




HBL2613SW




HBL2623




HBL2613ST



HBL2613VY



HBL2610SW



HBL2610ST



HBL2620SR

Dimensions in Inches (mm)