



Plugs

Description	Cord Diameter	Catalog Number	
Insulgrip® Plug, black and white nylon.	.230"-.720" (5.8-18.3)	HBL5666C	HBL5466C
EdgeConnect® Insulgrip plug, black and white, spring termination.	.230"-.720" (5.8-18.3)	HBL5666CST	HBL5466CST
EdgeConnect Insulgrip Plug, corrosion resistant, yellow nylon.	.230"-.720" (5.8-18.3)	HBL56CM66C	HBL54CM66C
Insulgrip plug, corrosion resistant, spring termination, yellow.	.230"-.720" (5.8-18.3)	HBL56CM66CST	HBL54CM66CST
8-Position Insulgrip Angle Plug, black and white nylon.	.325"-.655" (8.3-16.6)	HBL5666CA	HBL5466CA
Valise® Plug, yellow nylon.	.220"-.660" (5.6-16.8)	HBL5666VY	HBL5464VY




HBL5666C




HBL5666CST



HBL5669C




HBL5666CA



HBL5666VY



HBL5669VY



HBL5678C



Connector Bodies

Description	Cord Diameter	Catalog Number	
Insulgrip Connector Body, black and white nylon, multiple drive screws.	.230"-.720" (5.8-18.3)	HBL5669C	HBL5469C
EdgeConnect Insulgrip Connector Body, Black and White, Spring Termination.	.230"-.720" (5.8-18.3)	HBL5669CST	HBL5469CST
Valise Connector Body, yellow nylon.	.220"-.660" (5.6-16.8)	HBL5669VY	HBL5469VY

Note: See page B-54 for accessories.



Insulgrip Flanged Inlets

Description	Catalog Number	
Nylon casing, back wired.	HBL5678C	HBL5478C

Note: Flanged inlets are not HP rated. See page B-53 and B-54 for accessories.



Flanged Receptacles

Description	Catalog Number	
Nylon casing, multiple drive screws.	HBL5679C	HBL5479C
Stainless steel flange, brown phenolic housing (mounting screws packaged separately).	HBL5656	—

Note: Connector bodies are not HP rated. See pages B-53 and B-54 for accessories.

For quick visual identification of circuits or configurations.

Colored Cord Clamps*

Description	Color	Catalog Number
For use with 15A and 20A, 2 pole/3 wire, Insulgrip plugs and connectors with cord diameter range of .230"-.720" (5.8-18.3) only.	Blue	HBLCORDCLAMPBL
	Green	HBLCORDCLAMPGN
	Orange	HBLCORDCLAMPOR
	Purple	HBLCORDCLAMPP
	Red	HBLCORDCLAMPR
	Yellow	HBLCORDCLAMPY

Note: *Clamp only. Contains no screws. Order in increments of 10. Not UL Listed or CSA Certified.

Dimensions in Inches (mm)