

Locking Devices, Hubbellock, Industrial,
Female Connector Body, 60A 600V AC, 3-
Pole 4-Wire Grounding, Non NEMA, Screw
Terminal, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL26418](#)

Locking Devices, Hubbellock, Industrial, Female Connector Body,
60A 600V AC, 3-Pole 4-Wire Grounding, Non NEMA, Screw
Terminal, Yellow

Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with stainless steel screws provide maximum termination strength and dependability
- Insulated, color coded metallic housing enhances safety and abuse resistance

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage Withstand - 2,000V minimum, Environmental - Flammability - UL 94 VO, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #8 AWG - #4 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	• Certified to CSA C22.2 No. 42 • Listed to UL 498

Conductor

Number Of Wires	4-Wire
Wire Size	#8 AWG to #4 AWG
Number Of Poles	3-Pole
Cable Range	0.920 - 1.450 in

Current

Amperage Rating	60 A
Voltage Rating Description	600 V



Dielectric Strength	Withstands 2,000V minimum
Current Rating	60 A
Voltage Rating	600 V
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	60 A

Dimensions

Length	3.19 in
Display Size	Standard
Weight	2.45 lb.
Height	5.44 in
Width	1.09 in
Dimensions	3.19 in x 1.09 in x 5.44 in

General

Color	Yellow
Cord Range	0.920"-1.450" (23.36-36.83)
Specifications	• Connector Interior - Phenolic • Contacts / Springs - Copper alloy • Cord Clamp - Steel • Device Color - Yellow • Housing - Steel Housing / Yellow Polycarbonate Cover • Terminal - Copper • Terminal Screws - Stainless steel
UPC	783585017310
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	60A Grounding Hubbellock® Connector
Material	Steel

Logistics

Pallet Quantity	770
Carton Quantity	5

Operational

Operating Temperature

Maximum continuous 75°C and
minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand