

Locking Devices, Hubbellock, Industrial,
Male Plug, 60A 600V AC, 3-Pole 4-Wire
Grounding, Non NEMA, Screw Terminal,
Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL26419](#)

Locking Devices, Hubbellock, Industrial, Male Plug, 60A 600V
AC, 3-Pole 4-Wire Grounding, Non NEMA, Screw Terminal, Yellow

Features

- Molded-in male contacts are resistant to damage and provide a consistently positive connection
- Insulated, color coded metallic housing enhances safety and abuse resistance
- Box terminals in conjunction with stainless steel terminal screws provide maximum termination strength and dependability

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage Withstand - 2,000V minimum, Environmental - Flammability - HB or better, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #8 AWG - #4 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance	CM
Status	
EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	• Certified to CSA Standard • Listed to UL Standard

Conductor

Number Of Wires	4-Wire
Wire Size	#8 AWG to #4 AWG
Number Of Poles	3-Pole
Cable Range	0.920 - 1.450 in

Current

Amperage Rating	60 A
Voltage Rating Description	600 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	60 A



Voltage Rating	600 V
Current / Amperage Rating	60 A

Dimensions

Length	3.03 in
Weight	2.1 lb.
Height	5.90 in
Width	3.03 in
Dimensions	3.03 in x 3.03 in x 5.90 in

General

Color	Yellow
Cord Range	0.920"-1.450"(23.36-36.83)
Specifications	• Assembly Screws - Stainless Steel • Contacts - Brass • Cord Clamp Material - PET • Device Color - Black/White • Housing - Nylon • Plug Housing - Thermoset • Terminal Screws - Zinc plated steel
UPC	783585017327
Type	Plugs
Item Type	60A Hubbellock® Plug
Material	Nylon

Logistics

Pallet Quantity	770
Carton Quantity	5

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)