

HUBBELL
Wiring Device-Kellems

**Locking Devices, Hubbellock, Industrial,
Flanged Receptacle, 60A 600V AC, 4-Pole
5-Wire Grounding, Non NEMA, Screw
Terminal, Blue**

By Hubbell Wiring Device-Kellems
Catalog # [HBL26521](#)

Hubbellock Industrial Flanged Receptacle 60A



Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with stainless steel terminal screws provide maximum termination strength and dependability
- Metallic housing provides protection from damage in harsh environments

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Environmental - Flammability - UL 94 V0 for Receptacles and Inlets.HB or better for Plugs and Connectors, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C,Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #8 AWG - #4 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications


Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	• Certified to CSA Standard • Listed to UL Standard

Conductor

Number Of Wires	5-Wire
Wire Size	#8 AWG to #4 AWG
Number Of Poles	4-Pole

Current

Amperage Rating	60 A
Voltage Rating Description	600 VAC
Dielectric Strength	Withstands 2,000V minimum



Current Rating	60 A
Voltage Rating	600 VAC
Connectivity	Screw Terminals
Phase	Multi Phase
Current / Amperage Rating	60 A

Dimensions

Length	4.12 in
Display Size	Standard Sized Product
Weight	2.1 lb.
Height	4.53 in
Width	2.87 in
Dimensions	4.12 in x 2.87 in x 4.53 in

General

Specifications	• Contacts / Springs - Copper alloy • Flanged Housing - Zinc plated steel • Receptacle Interior - Phenolic • Terminal - Copper • Terminal Screws - Stainless steel
UPC	783585017525
Type	Flanged Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	60A Grounding Hubbellock® Flanged Receptacle
Material	Steel, Zinc Plated

Logistics

Carton Quantity	5
-----------------	---

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)