

Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 30A 600V AC, 2-Pole 3-Wire Grounding, L9-30R, Screw Terminal, Black and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL2653](#)

Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 30A 600V AC, 2-Pole 3-Wire Grounding, L9-30R, Screw Terminal, Black and White

Features

- Superior cord grip design protects terminations from excess strain.
- Clear, funnel shaped wire entry for ease of termination.
- Integral dust shield protects wiring chamber from dust or contaminants.

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L9-30R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole
Cable Range	0.325 - 0.930 in

Current

Amperage Rating	30 A
-----------------	------



Voltage Rating Description	600 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	600 VAC
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A

Dimensions

Length	2.26 in
Display Size	Standard
Weight	0.35 lb.
Height	3.86 in
Width	2.26 in
Dimensions	2.26 in x 2.26 in x 3.86 in

General

Color	Black, White
Specifications	• Assembly Screws - Steel - nickel plated • Contacts - Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)
UPC	783585039053
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	30A Grounding Insulgrip® Connector
Material	Nylon

Logistics

Carton Quantity	30
-----------------	----

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with
--------------------	--

Operating Temperature

impact.
Maximum continuous 75°C and
minimum -40°C without Impact

Product Assets

- Catalog [English]
- Catalog Page [English]
- Installation Manual [Spanish]



A Hubbell brand