

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, Single Flush
Receptacle, 30A, 125/250V AC, 3 Pole, 3
Wire Non-Grounding, NEMA L10-30R,
Nylon face, back and side wire**

By Hubbell Wiring Device-Kellems
Catalog # [HBL2660](#)

Locking Devices, Twist-Lock®, Single Flush Receptacle, 30A,
125/250V AC, 3 Pole, 3 Wire Non-Grounding, NEMA L10-30R,
Nylon face, back and side wire, Black



Features

- Wire restraint recess for both back and side wiring, greatly reduces the possibility of loosening the terminal connection
- Face color coding by voltage facilitates locating and mating of proper devices
- All-brass mounting and grounding system provides a lower resistance ground path and greater resistance to corrosion than steel mounting systems

Application

Heavy Duty Industrial

Performance

Electrical-Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	L10-30R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	3-Pole

Current



A Hubbell brand

Amperage Rating	30 A
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	125/250 VAC
Connectivity	Back and Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	30 A

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

General

Color Specifications	Black • Base - Glass-Reinforced thermoplastic polyester (RTP) • Contacts - Brass • Face - Nylon • Mounting Strap - Brass • Terminal Screws - #10 - 32 Brass • UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
Listings	
UPC	783585456775
Material - Mounting Hardware	Screw Mounting
Item Type	30A Single Flush Receptacle
Material	Nylon

Logistics

Carton Quantity	30
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)