

Locking Devices, Twist-Lock®, Corrosion Resistant Insulgrip® Plug, 30A, 250V AC, 2 Pole, 3 Wire Grounding, NEMA L6-30P, Yellow nylon

By Hubbell Wiring Device-Kellems
Catalog # [HBL26CM21](#)

Locking Devices, Twist-Lock®, Corrosion Resistant Insulgrip® Plug, 30A, 250V AC, 2 Pole, 3 Wire Grounding, NEMA L6-30P, Yellow nylon

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance
- Superior cord grip design protects terminations from excess strain
- Integral dust shield protects wiring chamber from dust or contaminants.

Application

Extra Heavy Duty Industrial/Marine

Performance

Electrical-Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.6, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Environmental - Moisture Resistance - IP20 Suitability

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Corrosion Resistant
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L6-30P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Configuration

Cord Type	All Listed Portables
-----------	----------------------

Current

Amperage Rating	30 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	250 VAC
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	30 A

Dimensions

Length	2.75 in
Display Size	Standard Sized
Weight	0.25 lb.
Height	2.26 in
Width	2.26 in
Dimensions	2.75 in x 2.26 in x 2.26 in

General

Color	Yellow
Cord Range	0.360"-0.930" (9-24)
Specifications	• Assembly Screws - Stainless Steel • Blades - Nickel Plated Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Bronze (Phillips / Slotted / Robertson)

Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
----------	--

UPC	783585039107
Material - Mounting Hardware	Cord Mounted
Item Type	30A Corrosion Resistant Insulgrip® Plug
Material	Nylon



Logistics

Carton Quantity 30

Operational

Operating Temperature Maximum continuous 75°C and minimum -40°C without impact

Horsepower - Maximum 2

Product Assets

- Catalog [English]
- Catalog Page [English]
- Installation Manual [Spanish]



A Hubbell brand