

Locking Devices, Twist-Lock®, Safety Shroud, Male Plug, 30A 125/250V, 3-Pole 4-Wire Grounding, L14-30P, Screw Terminal, Black and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL2711S](#)

Locking Devices, Twist-Lock®, Safety Shroud, Male Plug, 30A 125/250V, 3-Pole 4-Wire Grounding, L14-30P, Screw Terminal, Black and White

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance.
- Superior cord grip design protects terminations from excess strain.
- Integral dust shield protects wiring chamber from dust or contaminants.

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L14-30P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	4-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	3-Pole
Cable Range	0.350 - 1.150 in

Configuration



Cord Type All Listed Portables

Current

Amperage Rating	30 A
Voltage Rating Description	125/250 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	125/250 V
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	30 A

Dimensions

Length	2.33 in
Display Size	Standard Sized
Weight	0.40 lb.
Height	4.21 in
Width	2.33 in
Dimensions	2.33 in x 2.33 in x 4.21 in

General

Color	Black, White
Cord Range	0.350"-1.150" (9-29)
Specifications	• Assembly Screws - Steel - nickel plated • Blades - Brass • Housing / Cord Clamp - Nylon • Safety-Shroud® - White PBT • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)
UPC	783585234700
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	30A Safety-Shroud® Plug
Material	Composite

Logistics

Carton Quantity	10	Product Assets
Operational		Catalog [English]
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact	Catalog Page [English]
Horsepower - Maximum	2(2)	Installation Manual [French, English]

