

Locking Devices, Twist-Lock®, Industrial, Male Plug, 30A 3-Phase 277/480VAC, 4-Pole 4-Wire Non-Grounding, L19-30P, Screw Terminal, Black and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL2761](#)

Locking Devices, Twist-Lock®, Industrial, Male Plug, 30A 3-Phase 277/480VAC, 4-Pole 4-Wire Non-Grounding, L19-30P, Screw Terminal, Black and White

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance.
- Superior cord grip design protects terminations from excess strain.
- Clear, funnel shaped wire entry for ease of termination.
- Integral dust shield protects wiring chamber from dust or contaminants.

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L19-30P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	4-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	4-Pole
Cable Range	0.350 - 1.150 in

Configuration



Cord Type	All Listed Portables
Current	
Amperage Rating	30 A
Voltage Rating Description	3 Phase WYE 277/480 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Voltage Rating	3 Phase WYE 277/480 VAC
Connectivity	Pressure Terminal Screws
Phase	3 Phase WYE
Current / Amperage Rating	30 A
Dimensions	
Length	2.33 in
Display Size	Standard Sized
Weight	0.3 lb.
Height	2.75 in
Width	2.33 in
Dimensions	2.33 in x 2.33 in x 2.75 in
General	
Cord Range	0.350"-1.150" (9-29)
Specifications	• Assembly Screws - Steel - nickel plated • Blades - Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)
UPC	783585039473
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	30A Non-Grounding Insulgrip® Plug
Material	Nylon
Logistics	

Pallet Quantity	3060	Horsepower - Maximum	5
Carton Quantity	30		
Operational		Product Assets	
Operating Temperature	Maximum continuous 75°C and minimum -40°C without impact	Catalog [English]	
		Catalog Page [English]	
		Installation Manual [English]	

