

Locking Devices, Twist-Lock®, Single Flush
Receptacle, 30A, 4 Pole, 5 Wire Grounding,
240/415 VAC, 3 Phase Y, NEMA L26-30R,
Black Nylon

By Hubbell Wiring Device-Kellems
Catalog # [HBL2800](#)

Locking Devices, Twist-Lock®,Single Flush Receptacle, 30A, 4
Pole, 5 Wire Grounding, 240/415 VAC, 3 Phase Y, NEMA L26-30R,
Black Nylon

Features

- High-impact, abuse-resistant nylon face
- Wire restraint recess for both back and side wiring, greatly reduces the possibility of loosening the terminal connection
- Face color coding by voltage facilitates locating and mating of proper devices
- All-brass mounting and grounding system provides a lower resistance ground path and greater resistance to corrosion

Performance

Electrical-Current Interrupting - Certified at full rated current,
Electrical - Dielectric Voltage - 2,000V minimum, Mechanical -
Terminal Accommodation - #16 AWG - #8 AWG stranded,
Mechanical - Terminal Identification - Terminals identified in
accordance with UL 498, Environmental - Flammability - HB or
better per UL94/CSA 22.2 No.0.17, Environmental - Operating
Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o
impact), Environmental - Moisture Resistance - IP20 Suitability

Specifications

Standards - RoHS Compliance	CM
Status	
Industry Standard(s)	WR Rating
EU RoHS Indicator	Contact Manufacturer



Conductor

Number Of Poles	4-Pole
Number Of Wires	5-Wire
Wire Size	#16 AWG to #8 AWG

Dimensions

Height	1.23 in
Length	2.38 in

General

Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
UPC	783585580357
Item Type	30A Single Flush Receptacle

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish\]](#)