

Locking Devices, Twist-Lock®, Insulgrip® Plug, 30A, 4 Pole, 5 Wire Grounding, 240/415 VAC, 3 Phase Y, NEMA L26-30P, Black and white Nylon

By Hubbell Wiring Device-Kellems  
Catalog # [HBL2801](#)

Locking Devices, Twist-Lock®, Insulgrip® Plug, 30A, 4 Pole, 5 Wire Grounding, 240/415 VAC, 3 Phase Y, NEMA L26-30P, Black and white Nylon

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance
- Superior cord grip design protects terminations from excess strain
- Clear, funnel shaped wire entry for ease of termination
- Integral, dust shield protects wiring chamber from dust or contaminants.

Performance

Electrical-Current Interrupting - Certified at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Environmental - Moisture Resistance - IP20 Suitability

Specifications

EU RoHS Indicator                      Contact Manufacturer

Conductor



|                 |                   |
|-----------------|-------------------|
| Number Of Poles | 4-Pole            |
| Number Of Wires | 5-Wire            |
| Wire Size       | #16 AWG to #8 AWG |

Dimensions

|            |                             |
|------------|-----------------------------|
| Height     | 2.75 in                     |
| Width      | 2.21 in                     |
| Length     | 2.21 in                     |
| Dimensions | 2.21 in x 2.21 in x 2.75 in |

General

|           |                                                                                                                |
|-----------|----------------------------------------------------------------------------------------------------------------|
| Listings  | <ul style="list-style-type: none"><li>• UL 498</li><li>• Fed.Spec. W-C-596</li><li>• CSA C22.2 No.42</li></ul> |
| UPC       | 783585580326                                                                                                   |
| Item Type | 30A Insulgrip® Plug                                                                                            |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 30 |
|-----------------|----|

Product Assets

[Catalog \[English\]](#)  
[Catalog Page \[English\]](#)  
[Installation Manual \[French, English\]](#)