

Locking Devices, Twist-Lock®, Insulgrip® Connector, 30A, 4 Pole, 5 Wire Grounding, 240/415 VAC, 3 Phase Y, NEMA L26-30R, Black and white Nylon

By Hubbell Wiring Device-Kellems
Catalog # [HBL2803](#)

Locking Devices, Twist-Lock®, Insulgrip® Connector, 30A, 4 Pole, 5 Wire Grounding, 240/415 VAC, 3 Phase Y, NEMA L26-30R, Black and white Nylon

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance
- Superior cord grip design protects terminations from excess strain
- Clear, funnel shaped wire entry for ease of termination
- Integral, dust shield protects wiring chamber from dust or contaminants.

Performance

Electrical-Current Interrupting - Certified at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Environmental - Moisture Resistance - IP20 Suitability

Specifications

EU RoHS Indicator Contact Manufacturer

Conductor



Number Of Poles	4-Pole
Number Of Wires	5-Wire
Wire Size	#16 AWG to #8 AWG

Dimensions

Height	3.86 in
Width	2.21 in
Length	2.21 in
Dimensions	2.21 in x 2.21 in x 3.86 in

General

Listings	• UL 498 • Fed.Spec. W-C-596 • CSA C22.2 No.42
UPC	783585580333
Item Type	30A Insulgrip® Connector

Logistics

Carton Quantity	30
-----------------	----

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[French, English\]](#)