

Locking Devices, Twist-Lock®, Insulgrip®
Inlet, 30A, 4 Pole, 5 Wire Grounding,
240/415 VAC, 3 Phase Y, NEMA L26-30P,
White Nylon

By Hubbell Wiring Device-Kellems
Catalog # [HBL2805](#)

Locking Devices, Twist-Lock®, Insulgrip® Inlet, 30A, 4 Pole, 5 Wire
Grounding, 240/415 VAC, 3 Phase Y, NEMA L26-30P, White Nylon

Features

- Impact resistant thermoplastic construction
- Backwired terminations for ease of installation
- #10-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Performance

Electrical-Current Interrupting - Certified at full rated current,
Electrical - Dielectric Voltage - 2,000V minimum, Mechanical -
Terminal Accommodation - #16 AWG - #8 AWG stranded,
Mechanical - Terminal Identification - Terminals identified in
accordance with UL 498, Environmental - Flammability - HB or
better per UL94/CSA 22.2 No.0.17, Environmental - Operating
Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o
impact), Environmental - Moisture Resistance - IP20 Suitability

Specifications

EU RoHS Indicator Contact Manufacturer

Conductor

Number Of Poles 4-Pole



Number Of Wires 5-Wire
Wire Size #16 AWG to #8 AWG

Dimensions

Height 2.27 in
Width 2.88 in
Length 2.88 in
Dimensions 2.88 in x 2.88 in x 2.27 in

General

Listings • UL 498
 • Fed.Spec. W-C-596
 • CSA C22.2 No.42
UPC 783585580340
Item Type 30A Insulgrip® Inlet

Logistics

Carton Quantity 10

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[French\]](#)