HUBBELL
Wiring Device-Kellems

Watertight Devices, Twist-Lock® Connector, 30A, 3 Phase 250V AC, 3 Pole, 4 Wire, Thermoplastic elastomer, NEMA L15-30R, Yellow



By Hubbell Wiring Device-Kellems
Catalog # HBL29W75

CONN, W/TIGHT, 3P 30A 250V, L15-30R, YL

Features

- Smooth body design minimizes collection points simplifying the wash down process
- Strain relief nut always seals on the body, minimizing debris collection
- Stainless steel hardware and corrosion-resistant connection points

Performance

Electrical - Current Interrupting - Rated for current interruption per UL498, Electrical - Dielectric Voltage - 2500V AC, Electrical - Max Working Voltage - As marked, Electrical - Temperature Rise - 30°C max per UL498 at rated current, Environmental - UV resistance - All exposed materials are UV stabilized, Environmental - Moisture Resistance - UL Listed 4, 4X, 12, 6, 6P, Environmental - Operating Temperatures - -40°C (without impact) to +60°C continuous, Mechanical - Cord Accommodation - 0.375"-1.000" (9.5-25.4)

Specifications

Standards - RoHS Compliance Status	CM
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L15-30R
Industry Standard(s)	Meets NEMA WD-1, WD-6 And ANSI Standards

Conductor

Number Of Wires	4-Wire
Wire Size	• Min Cords: 12/3 SJ, 16/3 S, 14/4 SJ, 18/4 S, 18/5 S • Max Cord: 8/3 S, 8/4 S, 10/5 S
Number Of Poles	3-Pole

Current

Amperage Rating	30 A
Voltage Rating Description	3 Phase 250 VAC
Voltage Rating	3 Phase 250 VAC
Current / Amperage Rating	30 A

Dimensions

Length	2.77 in
Height	5.67 in
Width	2.77 in
Dimensions	2.77 in x 2.77 in x 5.67 in

General

Color	Yellow
UPC	783585131887
Type	Connector Body
Item Type	30A Watertight Twist-Lock® Connector

Logistics

Pallet Quantity	400
Carton Quantity	10

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved