

Locking Devices, Twist-Lock®, Marine Grade, Hull Inlet, 30A 125V, 2-Pole 3-Wire Grounding, L5-30R, Screw Terminal, Stainless Steel

By Hubbell Wiring Device-Kellems
Catalog # [HBL303SSO](#)

Locking Devices, Twist-Lock®, Marine Grade, Hull Inlet, 30A 125V, 2-Pole 3-Wire Grounding, L5-30R, Screw Terminal, Stainless Steel

Features

- New quick connect with backwards compatibility

Application

Marine Wiring Devices

Performance

Environmental - Moisture Resistance - IP56 Suitability

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Weather Resistant
EU RoHS Indicator	No
Nema Rating	L5-30R
Industry Standard(s)	• UL Listed • WR Rating

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	30 A
Current Rating	30 A
Voltage Rating	125 VAC



Wattage	3750
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	30 A

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

General

Color	Metallic
Specifications	• Dia.of Mounting Holes - 2.38 in. (60.3) • Housing Type - Traditional Metallic • Product Type - Shore Power Outlets
UPC	783585040677
Material - Mounting Hardware	Screw Mounting
Item Type	Single
Material	Stainless Steel, Composite

Logistics

Carton Quantity	5
-----------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)