

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 20A 250V, 2-Pole 2-Wire Non Grounding, L2-20R, Screw Terminal, Steel

By Hubbell Wiring Device-Kellems
Catalog # [HBL3226](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 20A 250V, 2-Pole 2-Wire Non Grounding, L2-20R, Screw Terminal, Steel

Features

- Heat resistant thermoset construction
- Stainless steel casing
- #8-32 terminal screws
- Mounting screws included

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 - #10 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	L2-20R
Industry Standard(s)	• Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	2-Wire
Wire Size	#16 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VAC



Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	2.25 in
Display Size	Standard Sized Product
Weight	0.25 lb.
Height	1.83 in
Width	2.25 in
Dimensions	2.25 in x 2.25 in x 1.83 in

General

Specifications	• Contacts - Brass / Bronze • Flange - Stainless steel • Mounting Screw - Nickel plated brass • Terminal Screws - Brass
UPC	783585236292
Type	Flanged Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Flanged Receptacles
Material	Nylon

Logistics

Pallet Quantity	4500
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)