

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, Industrial,
Flanged Receptacle, 20A 125/250V, 3-Pole
3-Wire Non Grounding, Non-NEMA, Screw
Terminal, White**

By Hubbell Wiring Device-Kellems
Catalog # [HBL3326C](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle,
20A 125/250V, 3-Pole 3-Wire Non Grounding, Non-NEMA, Screw
Terminal, White



Features

- Impact resistant thermoplastic construction
- Backwired terminations for ease of installation
- #10-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Application

Insulgrip

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	Non-NEMA

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	125/250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125/250 VAC
Connectivity	Back Wired Screw Terminals

Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	2.88 in
Display Size	Standard Sized Product
Weight	0.3 lb.
Height	1.93 in
Width	2.88 in
Dimensions	2.88 in x 2.88 in x 1.93 in

General

Specifications	• Assembly Screws - Steel - nickel plated • Contacts - Brass • Housing - Nylon • Terminal Clamp - Cold rolled steel – nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)
UPC	783585039800
Type	Flanged Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	20A Non-Grounding Insulgrip® Flanged Receptacle
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)



A Hubbell brand