

Locking Devices, Twist-Lock®, Marine Grade, Hull Inlet, 32A 230V AC 50 Cycles, 2-Pole 3-Wire Grounding, International, Screw Terminal, White

By Hubbell Wiring Device-Kellems
Catalog # [HBL332NM](#)

Locking Devices, Twist-Lock®, Marine Grade, Hull Inlet, 32A 230V AC 50 Cycles, 2-Pole 3-Wire Grounding, International, Screw Terminal, White

Features

- New quick connect with backwards compatibility
- Self-closing Cover
- Thermoset Contact Carrier
- Corrosion Resistant Rear enclosure

Application

Marine Wiring Devices

Performance

Environmental - Moisture Resistance - IP56 Suitability

Specifications

Environmental Conditions	Watertight
EU RoHS Indicator	No
Industry Standard(s)	CE Certified

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#12 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	32 A
Dielectric Strength	Withstands 3000V Minimum in
Current Rating	32 A
Voltage Rating	230V kV
Wattage	7360
Connectivity	Pressure Terminal Screws
Phase	Single Phase



Current / Amperage Rating	32 A
---------------------------	------

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

General

Color	White
Specifications	• Blade Type - Locking • Housing Type - Non-Metallic • Product Type - International Shore Power • Version - Inlet
UPC	783585040622
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	Hull Mount Single
Material	Thermoplastic

Logistics

Carton Quantity	5
-----------------	---

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact
--------------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)