

**30A, 125/250V,
3 Pole, 4 Wire Grounding,
Receptacles and Plugs**

IP20
SUITABILITY




30A 125/250V
NEMA 14-30R
2(2) HP



30A 125/250V
NEMA 14-30P
2(2) HP



Description	Cord Diameter	Catalog Number	
EV Grade receptacle, weather resistant, black RTP.	-	HBL9430A	-
EV Grade plug, black and white nylon.	.625"-1.310" (15.9-33.3)	-	HBL9431C
EV Grade angle plug, 4-position, black and white nylon.	.625"-1.310" (15.9-33.3)	-	HBL9432C



HBL9430A

**30A, 3Ø 250V AC,
3 Pole, 4 Wire Grounding,
Receptacles and Plugs**

IP20
SUITABILITY




30A 3Ø 250V AC
NEMA 15-30R
3 HP



30A 3Ø 250V AC
NEMA 15-30P
3 HP

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP weather resistant.	-	HBL8430A	-
Plug, nylon.	.625"-1.310" (15.9-33.3)	-	HBL8431C
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	-	HBL8432C



HBL9431C



HBL9432C

 **30A, 3ØY 120/208V AC,
4 Pole, 4 Wire Non-Grounding,
Receptacles and Plugs**

IP20
SUITABILITY




30A 3ØY
120/208V AC
NEMA 18-30R
UL Listed
3 HP



30A 3ØY
120/208V AC
NEMA 18-30P
UL Listed
3 HP

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP weather resistant.	-	HBL8330A	-
Plug, nylon.	.625"-1.310" (15.9-33.3)	-	HBL8331C

Note: RTP is an abbreviation for reinforced thermoplastic polyester.
See pages B-55 and B-56 for accessories.



HBL8330A



HBL8331C

Dimensions in Inches (mm)