

HBL® Compact Extra Heavy Duty Max, Straight Blade Specification Grade Receptacles



HBL5252

Specifications

Receptacles	Part	Description
Typical Specification – Catalog No. HBL5252 Manufacturer's Identification – Hubbell HBL5252 Description – Straight Blade Duplex Receptacle Type – 2 Pole, 3 Wire, Grounding Rating – 15A, 125V Certification – UL Listed to UL 498 File E2186, Fed. Spec. WC596, Certified to CSA 22.2, No. 42 File 285	Receptacle Top Base Triple Wipe Power Contacts Wire Clamps Mounting Strap Line Terminal Screws Ground Screw Center Assembly Rivet Automatic Self-Grounding Clip Flat Head Mounting Screws	15A Nylon RTP* .032 in. (.8) Brass .062 in. (1.8) Steel .050 in. (1.3) Brass #8-32 Brass, Multiple Drive #8-32 Brass, Multiple Drive (Green) Brass Stainless Steel Steel-Zinc Plated

Performance

Electrical	
Dielectric Voltage Max. Working Voltage Current Interrupting Temperature Rise	Withstands 2,000V minimum. 125V or 250V as rated. Certified for current interrupting at full rated current. Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Mechanical	
Terminal Identification Terminal Accommodation Product Identification	Terminals identified in accordance with UL 498 (Brass, White, Green). #14-10 AWG stranded or solid copper conductor only. Ratings are a permanent part of the device.
Environmental – Material	
Flammability Operating Temperature	UL 94V-2. Maximum continuous 75°C; minimum -40°C (w/o impact).

Note: *Reinforced Thermoplastic Polyester.

Please consult the factory for product dimensions and specifications of other products listed in this catalog.

Dimensions in Inches (mm)