

Straight Blade Devices, Receptacles, 4-
Plex, Commercial/Industrial Grade, 2-Pole
3-Wire Grounding, 20A 125V, 5- 20R,
Brown, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [HBL420](#)

Straight Blade Devices, Receptacles, 4- Plex,
Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 20A
125V, 5- 20R, Brown, Single Pack

Features

- Anchor hole and loop feature secures solid wire for fast, easy terminations
- Triple wipe contacts
- Easily accessible break-off tabs for split wiring
- Three conductors energize all four outlets

Application

Industrial

Performance

Electrical: Current Interrupting: Capable of withstanding a fault level of 1000A, per UL498, Dielectric Voltage: Withstands 2,000V minimum, Mechanical: Product Identification: Ratings are a permanent part of the device, Terminal Accommodation: #12 AWG stranded or solid copper conductor only, Terminal Identification: Terminals identified in accordance with UL 498 and CSA, Environmental: Flammability: UL 94 V-2, Operating Temperatures: Maximum continuous 75°C, minimum -40°C (w/o impact)

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-20R
Industry Standard(s)	• Certified to CSA 22.2, No. 42 File 285 • Listed to UL Standard 498 File E2186 • NEMA® WD-6 Compliant

Conductor

Number Of Wires	3-Wire
Wire Size	#12 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	20 A
Voltage Rating	125 V
Wattage	2500 W
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	4.30 in
Display Size	Standard Sized Product
Weight	0.4 lb.
Height	4.30 in
Width	0.92 in
Dimensions	4.30 in x 0.92 in x 4.30 in

General

Color	Brown
Series	4-Outlet Receptacle
Specifications	• Base - PBT • Face - Polycarbonate • Ground Contacts - .031 in. (.8) Brass • Ground Plate - .032 in. (.8) Plated Steel • Power Contacts - .032 in. (.8) Brass
UPC	783585014098
Material - Mounting Hardware	Screw Mounting
Item Type	4-PLEX
Material	Polycarbonate

Logistics

Pallet Quantity	1440
Carton Quantity	5

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1.00

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand