

4-PLEX, Hospital Grade Surge Suppression
Receptacle, 20A 125V, 5-20R, with Surge,
Blue

By Hubbell Wiring Device-Kellems
Catalog # [HBL420HS](#)

4-PLEX, Hospital Grade Surge Suppression Receptacle, 20A 125V,
5-20R, with Surge, Blue

Features

- Mounts directly to 4-inch square box
- Heavy duty, impact resistant housing
- Removable knockouts for mounting
- Heavy duty, triple wipe, brass power and ground contacts

Application

4-Plex with LED

Performance

Electrical - Frequency - 60Hz, Electrical - Protection Modes - Normal and Common Modes, Electrical - Response Time - Approximately 5 ns, Electrical - Transient Suppression - Peak Energy (10 X 100 μ s), Peak Current (8 X 20 μ s), Electrical - Voltage - 20V AC + 10% - 15%, Environmental - Flammability - UL 94V-2, Environmental - Operating Temperature - -40°F to 140°F (-40°C to 60°C)

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	5-20R
Industry Standard(s)	• Certified to CSA 22.2, No. 42 File 285 • Listed to UL Standard 498 File E2186

Current

Frequency Rating	60 Hz
Amperage Rating	20 A
Voltage Rating Description	125 V
Current Rating	20 A
Voltage Rating	125 V
Connectivity	Terminal Screws
Phase	Single Phase
Current / Amperage Rating	20 A



Dimensions

Display Size	Standard
--------------	----------

General

Color	Blue
Outlet	Straight Blade
Series	Hospital Grade
OEM Brand Name	Hubbell Wiring Device-Kellems
Specifications	• Base Material - Lexan® • Contact Design - Triple Wipe • Face Material - Lexan® • Mounting Screws - Brass • Power Contacts - .032 in. (.8) Brass
UPC	783585017891
Type	4-Plex
Material - Mounting Hardware	Mounting Screws
Item Type	Surge Protection Receptacles
Material	Composite

Logistics

Carton Quantity	5
-----------------	---

Operational

Response Time	5
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Indicator(s) Type	LED Only

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)