

EdgeConnect™ Twist-Lock® Series, Locking
Devices, 15A 250V, Black

By Hubbell Wiring Device-Kellems
Catalog # [HBL4550ST](#)

Locking Devices, EdgeConnect™ Twist-Lock®, Industrial, Duplex
Receptacle, 15A 250V, 2-Pole 3-Wire Grounding, L6-15R,
Screwless Terminal, Black

Features

- Faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Funnel shaped wire entry for ease of termination.

Application

Industrial

Specifications

Industry Standard(s)	• Listed to UL 498, Fed.Spec. W-C-596, Certified to CSA C22.2 No.42 • WR Rating
Environmental Conditions	IP20 Suitability
Nema Rating	L6-15R

Conductor

Contact	Brass
Number Of Wires	3
Number Of Poles	2

Current

Phase	Single Phase
Dielectric Strength	Withstands 2,000V minimum
Current / Amperage Rating	15 A
Current Interrupting	Certified for current interrupting at full rated current



Voltage Rating	250 VAC
Dimensions	
Size	Standard Sized Product
General	
Type	Receptacle
Series	EdgeConnect™ Twist-Lock® Series
U_Flammability	HB or better per UL94/CSA 22.2 No.0.17
Material	Nylon
U_Face	Polycarbonate
UPC	783585730875
Style	Locking Devices
Color	Black
Mounting Type	Screw Mount

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	Maximum Continuous 75°C, Minimum -40°C (w/o impact)
--------------------	--

Product Assets

- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)