

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, Industrial,
Flanged Receptacle, 15A 250V, 2-Pole 3-
Wire Grounding, L6-15P, Screw Terminal,
White**

By Hubbell Wiring Device-Kellems
Catalog # [HBL4586](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 15A
250V, 2-Pole 3-Wire Grounding, L6-15P, Screw Terminal, White



Features

- Heat resistant thermoset construction
- Stainless steel casing
- #5-40 terminal screws
- Mounting screws included

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #10 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications


Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L6-15P
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec.W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	250 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A



Voltage Rating	250 V
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	2.31 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.09 in
Width	1.75 in
Dimensions	2.31 in x 1.75 in x 1.09 in

General

Color	Black
Specifications	• Blades - Brass • Flange - Stainless steel • Mounting Screw - Nickel plated brass • Terminal Screws - Brass
UPC	783585236704
Type	Flanged Inlet
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	15A Grounding Stainless Steel Flanged Inlet
Material	Stainless Steel

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)