

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, VariLoad,
Male Plug, 20A 3-Phase Wye 120/208V AC-
400Hz, Non-NEMA, Screw Terminal,
Unique Center Pin**

By Hubbell Wiring Device-Kellems
Catalog # [HBL45915](#)

Locking Devices, Twist-Lock®, VariLoad, Male Plug, 20A 3-Phase
Wye 120/208V AC- 400Hz, 4-Pole 5-Wire Grounding, Non-
NEMA, Screw Terminal, Black, Unique Center Pin



Features

- Heat resistant thermoset construction
- Non-interchangeable center pin configuration to be designated to different circuits

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstand 2,000V minimum, Environmental - Flammability - HB or better per UL 94 or CSA 22.2 No. 0.6, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #14 AWG - #10 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	Listed to UL 498

Conductor


Number Of Wires	5-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	4-Pole
Cable Range	0.625 - 1.00 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------

Current

Amperage Rating	20 A
Voltage Rating Description	3 Phase WYE 120/208 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	3 Phase WYE 120/208 VAC



Connectivity	
Phase	
Current / Amperage Rating	

Screw Terminals	
Three Phase	
20 A	

Dimensions

Length	2.13 in
Display Size	Standard Sized
Weight	0.4 lb.
Height	3.79 in
Width	2.13 in
Dimensions	2.13 in x 2.13 in x 3.79 in

General

Color	Black
Cord Range	0.625"-1.00"
Specifications	• Assembly Screws - Brass • Blades - Brass • Cord Clamp - Zinc Plated Steel • Cover - Molded thermoset • Housing - Molded Thermoset • Terminal Screw - Brass
UPC	783585238104
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	20A Variload® Plug
Material	Composite

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)