

Locking Devices, Twist-Lock®, VariLoad,
Female Connector Body, 20A 3-Phase Wye
120/208V AC- 400Hz, Non-NEMA, Screw
Terminal, Unique Center Pin

By Hubbell Wiring Device-Kellems
Catalog # [HBL45935](#)

Locking Devices, Twist-Lock®, VariLoad, Female Connector Body,
20A 3-Phase Wye 120/208V AC- 400Hz, 4-Pole 5-Wire
Grounding, Non-NEMA, Screw Terminal, Black, Unique Center Pin

Features

- Heat resistant thermoset construction
- Non-interchangable center pin configuration to be designated to different circuits

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL 94 or CSA 22.2 No. 0.6, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #14 AWG - #10 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	Listed to UL 498

Conductor

Number Of Wires	5-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	4-Pole
Cable Range	0.625 - 1.00 in

Current

Amperage Rating	20 A
Voltage Rating Description	3 Phase WYE 120/208 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	3 Phase WYE 120/208 VAC
Connectivity	Pressure Terminal Screws
Phase	Three Phase



Current / Amperage Rating	20 A
Dimensions	
Length	2.13 in
Display Size	Standard
Weight	0.5 lb.
Height	3.79 in
Width	2.13 in
Dimensions	2.13 in x 2.13 in x 3.79 in
General	
Color	Black
Cord Range	0.625"-1.00"
Specifications	• Assembly Screws - Brass • Contacts - Brass • Cord Clamp - Zinc Plated Steel • Cover - Molded thermoset • Housing - Molded Thermoset • Terminal Screw - Brass
UPC	783585238159
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	20A Variload® Connector
Material	Composite
Logistics	
Carton Quantity	10
Operational	
Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand