

HUBBELL
Wiring Device-Kellems

**Heavy Duty Products, IEC Pin and Sleeve
Devices, Industrial Grade, Female
Connector Body, 60A 3-Phase Delta 250V
AC, Watertight, 3/4" NPT Liquidtight
Threading**

By Hubbell Wiring Device-Kellems
Catalog # [HBL460C9WLT](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial
Grade, Female Connector Body, 60A 3-Phase Delta 250V AC, 3-
Pole 4-Wire Grounding, Terminal Screws, Blue, Watertight



Features

- Insulated Non-Metallic housing
- Color coded housings by voltage for easy identification
- Corrosion-resistant self-closing gasketed cover

Application

High Ampacity Connections

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstand 3000V AC, Electrical - Max. Working Voltage - 600V RMS, Environmental - Flammability - HB or better per UL 94 or CSA C22.2 No. 0.17, Environmental - Ingress Protection - IP67 Suitability, Environmental - Moisture Resistance - Watertight per IEC 60309-1, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum - 40°C w/o impact, Mechanical - Impact Resistance - Per CSA C22.2 No. 182.1 / UL1682, Mechanical - Product Identification - Ratings are a permanent part of the device housing, Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

Specifications

Environmental Conditions	Watertight
EU RoHS Indicator	Yes
Industry Standard(s)	• CSA Certified File LR280C • UL Classified to IEC 60309-1 IEC 60309-2 • UL Listed, File E146033
Nema Rating	Non-NEMA

Conductor

Number Of Wires	4-Wire
Number Of Conductors	4-Wire Grounding
Conductor Range	#8 AWG to #2 AWG
Number Of Poles	3-Pole

Current



Dielectric Strength	Withstands 3000V Minimum in
Voltage Rating Description	3 Phase 250 VAC
Current / Amperage Rating	60 A
Connectivity	Pressure Terminal Screws

Dimensions

Display Size	Standard
--------------	----------

General

Series	HBL Heavy Duty
Style	Standard Service
Color	Blue
Item Type	Standard
Insulation	Insulated Body
Material - Mounting Hardware	Cord Mounted
Type	Watertight Connector Body
Specifications	• Cord Clamps - Reinforced Thermoplastic Polyester • Covers - Reinforced Thermoplastic Polyester • Gaskets - Solid Neoprene • Glands - Solid Neoprene • Housing - Zytel® ST801 Nylon
UPC	783585550336

Logistics

Carton Quantity	10
Pallet Quantity	180

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
--------------------	--

Product Assets

[Catalog Page \[English\]](#)
[Installation Manual \[French, English\]](#)