

## Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male, Plug, 60A 125/250V, 3-Pole 4-Wire Grounding, Watertight- Reversed Service

By Hubbell Wiring Device-Kellems  
Catalog # [HBL460P12WR](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male, Plug, 60A 125/250V, 3-Pole 4-Wire Grounding, Terminal Screws, Orange, Watertight- Reversed Service



### Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 3,000V AC Min
- Electrical - Max. Working Voltage - 600V AC RMS
- Environmental - Flammability - HB or Better per UL 94 or CSA C22.2 No. 0.17
- Environmental - Ingress Protection - IP67 Suitability
- Environmental - Moisture Resistance - Watertight per IEC 60309-1
- Environmental - Operating Temperature - Maximum Continuous 75°C
- Minimum - 40°C w/o impact
- Mechanical - Impact Resistance - Per CSA C22.2 No. 182.1 / UL1682
- Mechanical - Product Identification - Identification and ratings are a permanent part of the device housing.
- Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

### General

Catalog Number	HBL460P12WR
Color	Orange
EU RoHS Indicator	Yes
Environmental Conditions	Watertight
Item Type	Male Plug- Reversed
Material	Composite
Material - Mounting Hardware	Cord Mounted
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Series	Non-Fused
Specifications	<ul style="list-style-type: none"><li>• Contact Carrier - High-Impact Thermoset</li><li>• Housing - Zytel® ST801 Nylon</li><li>• Locking Ring - Reinforced Thermoplastic Polyester</li></ul>

Style  
Type  
UPC

- Retainer - High-Impact Thermoset
  - Terminal Screws - Stainless Steel
- Reverse Service  
Watertight Mating Plug  
783585012728

### Dimensions

Display Size Standard Sized

### Electrical Ratings

Amperage Rating	60 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	60 A
Current Rating	60 A
Phase	Single Phase
Voltage Rating	120/240 VAC
Voltage Rating Description	120/240 VAC

### Conductor Related

Cord Type	All Portable
Number Of Wires	4-Wire
Wire Size	#8 AWG to #2 AWG

### Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"><li>• CSA Standard C22.2 No. 182.1</li><li>• UL Classified to IEC60309-1</li><li>• UL Listed, File E146032</li></ul>
Nema Rating	Non-NEMA

### Logistics

Carton Quantity	10
-----------------	----

### Product Assets

Catalog Page - WDK G-22 Catalog Page  
Catalogs - WDK Catalog Full 2024  
Engineering Drawing - HBL460P12WR AutoCAD Drawing  
Installation Manuals - WIRING\_PD1303\_INSTALLINST  
Literature - PULP & PAPER SOLUTIONS

Literature - IEC Pin & Sleeve Devices  
Literature - Pulp & Paper Solutions  
Sales Drawings - WDK\_HBL460P\_DRAWING\_PDF  
Specifications - HBL460P12WR  
Warranty - Industrial & Commercial Products



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved  
WDK-HBL460P12WR-SPEC-EN | REV 7/2025