HUBBELL
Wiring Device-Kellems

# Locking Devices, Twist-Lock®, Valise, Female Connector Body, 15A 125V, 2-Pole 3-Wire Grounding, L5-15R, Screw Terminal, Yellow



By Hubbell Wiring Device-Kellems
Catalog # HBL4729VY

Locking Devices, Twist-Lock®, Valise, Female Connector Body, 15A 125V, 2-Pole 3-Wire Grounding, L5-15R, Screw Terminal, Yellow

## Features

- Two captive multiple drive assembly screws
- Totally insulated impact and crush resistant nylon body
- Powerful cord grips prevent conductor slippage and strain on wiring terminals

## Application

Heavy Duty Industrial

## Performance

Electrical - Current Interrupting - Certified for full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL 94 or CSA 22.2 No. 0.6, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperature - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #12 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

## Specifications

| | |
|---|---|
| Standards - RoHS Compliance Status | CM |
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| EU RoHS Indicator | Yes |
| Nema Rating | L5-15R |
| Industry Standard(s) | • Certified to CSA C22.2 No.42<br>• Fed.Spec. W-C-596<br>• Listed to UL 498 |

## Conductor

| | |
|---|---|
| Number Of Wires | 3-Wire |
| Wire Size | #18 AWG to #12 AWG |
| Number Of Poles | 2-Pole |
| Cable Range | 0.220 - 0.660 in |

## Current

| | |
|---|---|
| Amperage Rating | 15 A |
| Voltage Rating Description | 125 V |
| Dielectric Strength | Withstands 2,000V minimum |
| Current Rating | 15 A |
| Voltage Rating | 125 V |
| Connectivity | Pressure Terminal Screws |
| Current / Amperage Rating | 15 A |

## Dimensions

| | |
|---|---|
| Length | 1.50 in |
| Display Size | Standard |
| Weight | 0.15 lb. |
| Height | 2.59 in |
| Width | 1.50 in |
| Dimensions | 1.50 in x 1.50 in x 2.59 in |

## General

| | |
|---|---|
| Color | Yellow |
| Cord Range | 0.220"-0.660"(5.6-16.8) |
| Specifications | • Assembly Screws - Steel - Zinc plated<br>• Cable Inserts - Polyphenylene Oxide<br>• Contacts - Brass<br>• Housing - Nylon<br>• Terminal Clamp - Cold rolled steel – nickel plated<br>• Terminal Screws - #6-32 Brass (Phillips / Slotted / Robertson) |
| UPC | 783585236858 |
| Type | Connector Body |
| Material - Mounting Hardware | Cord Mounted |
| Insulation | Insulated Body |
| Item Type | 15A Valise® Connector |
| Material | Nylon |

## Logistics

| | |
|---|---|
| Carton Quantity | 10 |

## Operational

| | |
|---|---|
| Temperature Rating | • Maximum Continuous: 75° C<br>• Minimum Continuous: -40° C w/o impact, -25° with |

| | |
|---|---|
| | impact. |
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |

## Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [Spanish, French, English]

A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved