HUBBELL
Wiring Device-Kellems

Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 15A 277V AC, 2-Pole 3-Wire Grounding, L7-15R, Screw Terminal, Mounted to 4"Box Cover



By Hubbell Wiring Device-Kellems
Catalog # HBL4761

Twist-Lock® Industrial Flush Receptacle 15A Mounted to 4"Box Cover

Features

- Reinforced thermoplastic construction
- Single piece, all brass contacts
- All terminals are back and side wired
- Brass mounting strap with stainless steel grounding clip

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #10 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L7-15R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed. Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	277 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	277 VAC
Connectivity	Side Wired
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	4.12 in
Display Size	Standard Sized Product
Weight	0.25 lb.
Height	1.27 in
Width	4.12 in
Dimensions	4.12 in x 4.12 in x 1.27 in

General

Specifications	• Base - RTP • Clamp - Brass • Contacts - Brass • Face - RTP • Ground Contact - Brass • Terminal Screws - Brass
UPC	783585236896
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	15A Grounding Single Flush Receptacle
Material	Thermoplastic

Logistics

Carton Quantity	5

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	2

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved