

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 15A 277V AC, 2-Pole 3-Wire Grounding, L7-15R, Screw Terminal, Stainless Steel

By Hubbell Wiring Device-Kellems  
Catalog # [HBL4785](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 15A 277V AC, 2-Pole 3-Wire Grounding, L7-15R, Screw Terminal, Stainless Steel

Features

- Impact resistant thermoplastic construction
- Backwired terminations for ease of installation
- #8-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #10 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

|                          |                                                                                                                                        |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means                                                                                        |
| EU RoHS Indicator        | Yes                                                                                                                                    |
| Nema Rating              | L7-15R                                                                                                                                 |
| Industry Standard(s)     | <ul style="list-style-type: none"><li>• Certified to CSA C22.2 No.42</li><li>• Fed. Spec. W-C-596</li><li>• Listed to UL 498</li></ul> |

Conductor

|                 |                    |
|-----------------|--------------------|
| Number Of Wires | 3-Wire             |
| Wire Size       | #18 AWG to #10 AWG |
| Number Of Poles | 2-Pole             |

Current

|                 |      |
|-----------------|------|
| Amperage Rating | 15 A |
|-----------------|------|



|                            |                           |
|----------------------------|---------------------------|
| Voltage Rating Description | 277 VAC                   |
| Dielectric Strength        | Withstands 2,000V minimum |
| Current Rating             | 15 A                      |
| Voltage Rating             | 277 VAC                   |
| Connectivity               | Screw Terminals           |
| Phase                      | Single Phase              |
| Current / Amperage Rating  | 15 A                      |

Dimensions

|              |                             |
|--------------|-----------------------------|
| Length       | 2.31 in                     |
| Display Size | Standard Sized Product      |
| Weight       | 0.15 lb.                    |
| Height       | 1.36 in                     |
| Width        | 1.75 in                     |
| Dimensions   | 2.31 in x 1.75 in x 1.36 in |

General

|                              |                                                                                                                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Specifications               | <ul style="list-style-type: none"><li>• Blades - Brass</li><li>• Flange - Stainless steel</li><li>• Mounting Screw - Nickel plated brass</li><li>• Terminal Screws - Brass</li></ul> |
| UPC                          | 783585236971                                                                                                                                                                         |
| Type                         | Receptacle                                                                                                                                                                           |
| Material - Mounting Hardware | Screw Mounting                                                                                                                                                                       |
| Item Type                    | 15A Grounding Stainless Steel Flanged Receptacle                                                                                                                                     |
| Material                     | Nylon                                                                                                                                                                                |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Operational

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
|-----------------------|----------------------------------------------------------|

Product Assets

[Catalog \[English\]](#)  
[Catalog Page \[English\]](#)