

Straight Blade Devices, Miscellaneous
Receptacles, Display type, brown phenolic,
blank flush plug, 15A 125V, 2-Pole 3-Wire
Grounding, 5-15R, Brass.

By Hubbell Wiring Device-Kellems
Catalog # [HBL5236](#)

Straight Blade Miscellaneous Display type phenolic,blank flush
plug 15A

Features

- Miscellaneous Receptacles
- Display type
- brown phenolic
- blank flush plug

Application

Commercial Specification Grade

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - UL
94 V-2 or better, Environmental - Operating Temperatures -
Maximum continuous 75°C, minimum -40°C (w/o impact),
Mechanical - Product Identification - Ratings are a permanent
part of the device, Mechanical - Terminal Accommodation - #14-
#10 AWG copper stranded or solid conductor only, Mechanical -
Terminal Identification - Terminals identified in accordance with
UL 498 and CSA

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	5-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 File 285 • NEMA® WD-6 Compliant • UL Listed to UL498 File E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
-----------------	------



Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Wattage	1875 W
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	4.5 in
Display Size	Standard Sized Product
Weight	0.55 lb.
Height	1.8 in
Width	2.75 in
Dimensions	4.5 in x 2.75 in x 1.8 in

General

Color	Brass
Specifications	• Base - Phenolic • Face - Phenolic • Power Contacts - .032" (.81)
UPC	783585013787
Material - Mounting Hardware	Screw Mounting
Item Type	Special Application Receptacles

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[French, English\]](#)