

Straight Blade Devices, Receptacles,  
Duplex, Industrial Grade, 2-Pole 3-Wire  
Grounding, 15A 125V, 5-15R, Brown, Single  
Pack, Mounted to 4" Round Cover

By Hubbell Wiring Device-Kellems  
Catalog # [HBL5253](#)

Straight Blade Devices, Receptacles, Duplex, Industrial Grade, 2-  
Pole 3-Wire Grounding, 15A 125V, 5-15R, Brown, Single Pack,  
Mounted to 4" Round Cover

Features

- Slender/compact design
- Brass Mounting Strap
- Triple wipe contacts

Application

Extra Heavy Duty Compact

Performance

Electrical - Current Interrupting - Certified for current  
interrupting at full rated current, Electrical - Dielectric Voltage -  
Withstands 2,000V minimum, Environmental - Flammability - UL  
94 V-O, Environmental - Operating Temperatures - Maximum  
continuous 75°C, minimum -40°C (w/o impact), Mechanical -  
Product Identification - Ratings are a permanent part of the  
device, Mechanical - Terminal Accommodation - #14-#10 AWG  
copper stranded or solid conductor only, Mechanical - Terminal  
Identification - Terminals identified in accordance with UL 498  
and CSA

Specifications

|                          |                                                                                                                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environmental Conditions | Indoor Dry Unless Protected By<br>Additional Means                                                                                                                                                     |
| EU RoHS Indicator        | No                                                                                                                                                                                                     |
| Nema Rating              | 5-15R                                                                                                                                                                                                  |
| Industry Standard(s)     | <ul style="list-style-type: none"><li>• Certified to CSA 22.2, No. 42<br/>File 285</li><li>• Fed. Spec. WC596</li><li>• NEMA® WD-6 Compliant</li><li>• UL Listed to UL498 File No.<br/>E2186</li></ul> |

Conductor

|                 |                    |
|-----------------|--------------------|
| Number Of Wires | 3-Wire             |
| Wire Size       | #14 AWG to #10 AWG |
| Number Of Poles | 2-Pole             |

Current

|                            |                           |
|----------------------------|---------------------------|
| Amperage Rating            | 15 A                      |
| Voltage Rating Description | 125 V                     |
| Dielectric Strength        | Withstands 2,000V minimum |



|                           |                     |
|---------------------------|---------------------|
| Current Rating            | 15 A                |
| Voltage Rating            | 125 V               |
| Wattage                   | 1875 W              |
| Connectivity              | Back and Side Wired |
| Phase                     | Single Phase        |
| Current / Amperage Rating | 15 A                |

Dimensions

|              |                             |
|--------------|-----------------------------|
| Length       | 3.28 in                     |
| Display Size | Standard Sized Product      |
| Weight       | 0.3 lb.                     |
| Height       | 1.05 in                     |
| Width        | 1.33 in                     |
| Dimensions   | 3.28 in x 1.33 in x 1.05 in |

General

|                              |                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color                        | Brown                                                                                                                                                                                                                                                                                                                                                 |
| Specifications               | <ul style="list-style-type: none"><li>• Automatic Self-grounding<br/>Clip - Stainless steel</li><li>• Base - RTP</li><li>• Contacts - Brass</li><li>• Face - Nylon</li><li>• Mounting Screws - Steel-<br/>Zinc Plated</li><li>• Mounting Strap - .031" (.8)<br/>Brass</li><li>• Terminal Screws - Brass</li><li>• Wire Clamp - Plated brass</li></ul> |
| UPC                          | 783585014159                                                                                                                                                                                                                                                                                                                                          |
| Material - Mounting Hardware | Screw Mounting                                                                                                                                                                                                                                                                                                                                        |
| Item Type                    | Traditional Duplex                                                                                                                                                                                                                                                                                                                                    |
| Material                     | Nylon                                                                                                                                                                                                                                                                                                                                                 |

Logistics

|                 |   |
|-----------------|---|
| Carton Quantity | 5 |
|-----------------|---|

Operational

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Operating Temperature | Maximum continuous 75°C and<br>minimum -40°C without Impact |
| Horsepower - Maximum  | 0.5                                                         |

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

---



A Hubbell brand