

Straight Blade Devices, Receptacles,
Flanged, Commercial /Industrial Grade, 2-
Pole 3-Wire Grounding, 15A 125V, 5-15R,
brown, Single Pack.

By Hubbell Wiring Device-Kellems
Catalog # [HBL5256](#)

Straight Blade Devices, Receptacles, Flanged, Commercial
/Industrial Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R,
brown, Single Pack.

Features

- Stainless steel flange

Application

Heavy Duty

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - UL
94 V-0, Environmental - Operating Temperatures - Maximum
continuous 75°C, minimum -40°C (w/o impact), Mechanical -
Product Identification - Ratings are a permanent part of the
device, Mechanical - Terminal Accommodation - #14-#10 AWG
copper stranded or solid conductor only, Mechanical - Terminal
Identification - Terminals identified in accordance with UL 498
and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	5-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 • NEMA® WD-6 Compliant • UL Listed, File E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V



Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Wattage	1875 W
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Display Size	Standard Sized Product
Weight	0.15 lb.

General

Color	Brown
Cord Range	0.230"-0.720" (5.8-18.3)
Specifications	• Face - Phenolic • Mounting Screw - Nickel plated brass • Power Contacts - • .040" (1.0) Brass • Terminal Screw - #8-32 Brass, Multiple Drive
UPC	783585013046
Material - Mounting Hardware	Screw Mounting
Item Type	Flanged Single
Material	Stainless Steel

Logistics

Pallet Quantity	5000
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.50

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)