

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5- 15R, Ivory

By Hubbell Wiring Device-Kellems
Catalog # [HBL5260ISA](#)



Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5-15R, Ivory

Features

- Automatic self-grounding staple
- Distinctive surge symbol provides quick identification
- Power-on indicator light verifies that power is available
- Alert alarm sounds when surge protection is no longer functioning

Application

Decorator Duplex

Performance

- Electrical - Protection Modes - Normal and Common Modes
- Electrical - Response Time - Approximately 5 ns
- Electrical - Transient Suppression - Peak Energy (10 X 100 Qs), Peak Current (8 X 20 Qs)
- Electrical - Voltage - 120V AC + 10% - 15%
- Environmental - Flammability - UL 94V-2
- Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

General

Catalog Number	HBL5260ISA
Color	Ivory
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	None
Item Type	Surge Protection Receptacles
Material	Composite
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade
Response Time	5
Series	Specification Grade
Specifications	<ul style="list-style-type: none">• Base Material - Nylon• Contact Design - Tandem Modified Bypass• Face Material - Nylon

- Mounting Strap - .050" (1.3) Steel-Zinc Coated
- Power Contact - .031" (.8) Brass

Type	Duplex
UPC	783585060996

Dimensions

Display Size	Standard
--------------	----------

Electrical Ratings

Amperage Rating	15 A
Connectivity	Terminal Screws
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none">• CSA Certified to Specification C22.2 No. 42• Listed to UL Standards 498• UL Listed File E2186
Nema Rating	5-15R

Logistics

Carton Quantity	10
Pallet Quantity	3500

Product Assets

[Catalog Page - WDK M-13 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - HBL5260ISA AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD1152_INSTALLINST](#)
[Literature - SpikeShield® Surge Protective Devices](#)
[Literature - Residential Catalog](#)
[Literature - Residential Product Guide](#)



A Hubbell brand