

Straight Blade Devices, Receptacles,  
Combo Duplex, Commercial/Industrial  
Grade, 2-Pole 3-Wire Grounding, 15A 125V  
and 250V, 5-15R and 6-15R, Brown

By Hubbell Wiring Device-Kellems  
Catalog # [HBL5292](#)

Straight Blade Receptacle Combo Duplex 15A

Features

- Receptacles
- Combo Duplex
- Commercial/Industrial Grade
- 2-Pole 3-Wire Grounding

Application

Heavy Duty

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-2 or better, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

|                                    |                                                                                                                                    |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Standards - RoHS Compliance Status | CM                                                                                                                                 |
| Environmental Conditions           | Indoor Dry Unless Protected By Additional Means                                                                                    |
| EU RoHS Indicator                  | Yes                                                                                                                                |
| Nema Rating                        | 5-15R, 6-15R                                                                                                                       |
| Industry Standard(s)               | <ul style="list-style-type: none"><li>• Certified to CSA, C22.2, No. 42 File 285</li><li>• UL Listed to UL498 File E2186</li></ul> |

Conductor

|                 |                    |
|-----------------|--------------------|
| Number Of Wires | 3-Wire             |
| Wire Size       | #14 AWG to #10 AWG |
| Number Of Poles | 2-Pole             |

Current

|                 |      |
|-----------------|------|
| Amperage Rating | 15 A |
|-----------------|------|



|                            |                                                                         |
|----------------------------|-------------------------------------------------------------------------|
| Voltage Rating Description | <ul style="list-style-type: none"><li>• 125 V</li><li>• 250 V</li></ul> |
| Dielectric Strength        | Withstands 2,000V minimum                                               |
| Current Rating             | 15 A                                                                    |
| Voltage Rating             | 125/250 V                                                               |
| Wattage                    | 3750 W                                                                  |
| Connectivity               | Back and Side Wired                                                     |
| Phase                      | Single Phase                                                            |
| Current / Amperage Rating  | 15 A                                                                    |

Dimensions

|              |                            |
|--------------|----------------------------|
| Length       | 3.28 in                    |
| Display Size | Standard Sized Product     |
| Weight       | 0.2 lb.                    |
| Height       | 0.88 in                    |
| Width        | 1.5 in                     |
| Dimensions   | 3.28 in x 1.5 in x 0.88 in |

General

|                              |                                                                                                                                            |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Color                        | Brown                                                                                                                                      |
| Specifications               | <ul style="list-style-type: none"><li>• Base - Reinforced PET</li><li>• Face - Nylon</li><li>• Power Contacts - .037" (.9) Brass</li></ul> |
| UPC                          | 783585435404                                                                                                                               |
| Material - Mounting Hardware | Screw Mounting                                                                                                                             |
| Item Type                    | Combination Duplex Receptacles                                                                                                             |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Operational

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
| Horsepower - Maximum  | 1.5                                                      |

Product Assets

[Catalog \[English\]](#)  
[Catalog Page \[English\]](#)  
[Installation Manual \[English\]](#)