

Straight Blade Devices, Receptacles,
Commercial/Industrial Grade, 2-Pole 3-
Wire Grounding, 15A 125V, 5-15R Ivory,
Single Pack.

By Hubbell Wiring Device-Kellems
Catalog # [HBL5292I](#)

Straight Blade Devices, Receptacles, Commercial/Industrial
Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R Ivory, Single
Pack.

Features

- Receptacles
- Commercial/Industrial Grade
- 2-Pole 3-Wire Grounding
- 15A 125V

Application

Heavy Duty

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - UL
94 V-2 or better, Environmental - Operating Temperatures -
Maximum continuous 75°C, minimum -40°C (w/o impact),
Mechanical - Product Identification - Ratings are a permanent
part of the device, Mechanical - Terminal Accommodation - #14-
#10 AWG copper stranded or solid conductor only, Mechanical -
Terminal Identification - Terminals identified in accordance with
UL 498 and CSA

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 File 285 • UL Listed to UL498 File E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
-----------------	------



Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Wattage	3750 W
Connectivity	Back and Side Wired
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.25 lb.
Height	0.88 in
Width	1.5 in
Dimensions	3.28 in x 1.5 in x 0.88 in

General

Color	Ivory
Specifications	• Base - Reinforced PET • Face - Nylon • Face Style - Finder Groove
UPC	783585435428
Material - Mounting Hardware	Screw Mounting
Item Type	Combination Duplex Receptacles

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1.5

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)