

Heavy Duty Products, IEC Pin and Sleeve
Devices, Industrial Grade, Female
Connector, 30A 4-Pole 5-Wire Grounding,
Red, 4X and IP69k, 3/4" NPT Liquidtight
Threading

By Hubbell Wiring Device-Kellems
Catalog # [HBL530C6WLTM1](#)

Heavy Duty Products, IEC Pin and Sleeve

Features

- Insulated Non-Metallic housing
- Color coded housings by voltage for easy identification
- Corrosion-resistant self-closing gasketed cover

Application

High Ampacity Watertight Connections

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstand 3000V AC, Electrical - Max. Working Voltage - 600V RMS, Environmental - Flammability -V-O, Environmental - Ingress Protection - Type 3R, 3RX, 4X and IP68, IP69k Suitability, Environmental - Moisture Resistance - Watertight per IEC 60309-1, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum - 40°C w/o impact, Mechanical - Impact Resistance - Per CSA C22.2 No. 182.1 / UL1682, Mechanical - Product Identification - Ratings are a permanent part of the device housing, Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

Specifications

Environmental Conditions	Watertight
EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	• CSA Certified File LR280C • UL Classified to IEC 60309-1 IEC 60309-2 • UL Listed to UL1682
Nema Rating	Non-NEMA

Conductor

Number Of Wires	5-Wire
Wire Size	#12 AWG to #10 AWG
Number Of Conductors	5-Wire Grounding
Conductor Range	#12 AWG to #8 AWG



Number Of Poles	4-Pole
Current	
Dielectric Strength	Withstands 3000V Minimum in
Voltage Rating Description	• 200/346-240/415 V V • 220/380-240/415 V V
Phase	Multi Phase
Current / Amperage Rating	30 A
Connectivity	Pressure Terminal Screws

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

General

Series	HBL Heavy Duty
Style	Standard Service
Color	Red
Item Type	Standard
Insulation	Insulated Body
Material - Mounting Hardware	Cord Mounted
Type	Watertight Connector Body
Material	Thermoplastic
UPC	783585679860

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
--------------------	--

Product Assets

[Catalog Page \[English\]](#)
[Installation Manual \[French, English\]](#)