

Straight Blade Devices, Male Plug, Valise Series, Industrial/Commercial Grade, Straight, 2-Pole 3-Wire Grounding, 20A 125V, 5-20P, Black, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [HBL5364VBK](#)

Straight Blade Devices, Male Plug, Valise Series,
Industrial/Commercial Grade, Straight, 2-Pole 3-Wire Grounding,
20A 125V, 5-20P, Black, Single Pack

Features

- Hinged one piece body design for easy assembly
- Powerful, offsetting cord grips clamp on individual conductors
- Assembly screws are captive and will not fall out while wiring

Application

Industrial/Commercial Grade

Performance

Electrical:Current Interrupting: Certified for current interrupting at full rated current, Dielectric Voltage: Withstands 2,000V minimum, Mechanical :Terminal Accommodation #18-#12 AWG stranded copper wire only, Terminal Identification: Terminals identified in accordance with UL 498 and CSA, Environmental :Flammability: UL 94 HB or better, IP Suitability: IP20, Operating Temperatures: Maximum continuous 75°C, minimum -40°C (w/o impact)

Specifications

EU RoHS Indicator	Contact Manufacturer
Nema Rating	5-20P
Industry Standard(s)	• CSA Certified to C22.2 No 42 File 280C • NEMA® WD-6 Compliant • UL Listed to UL498 File E1706

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #12 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125 VAC
Connectivity	Screw Terminals



Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Weight	0.15 lb.
--------	----------

General

Color	Black
Style	Standard
Series	Valise®
Specifications	• Assembly Screws - Plated Steel • Assembly Screws - Plated steel • Blades - Brass • Cable Inserts - PPO • Housing - Nylon • Terminal Clamp - Nickel plated steel • Terminal Screws - #8-32 Brass , multiple drive
UPC	783585019222
Type	Plug
Material - Mounting Hardware	Cord Mounted
Item Type	Valise
Material	Polycarbonate

Logistics

Pallet Quantity	6000
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1.00

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)