

Straight Blade Devices, Female Connector Body, Valise Series, Industrial/Commercial Grade, Straight, 2-Pole 3- Wire Grounding, 20A 125V, 5-20R

By Hubbell Wiring Device-Kellems
Catalog # [HBL5369VBK](#)

Straight Blade Devices, Female Connector Body, Valise Series, Industrial/Commercial Grade, Straight, 2-Pole 3- Wire Grounding, 20A 125V, 5-20R, Black, Single Pack

Features

- Hinged one piece body design for easy assembly
- Powerful, offsetting cord grips clamp on individual conductors
- Assembly screws are captive and will not fall out while wiring

Application

Industrial/Commercial

Performance

Electrical:Current Interrupting: Certified for current interrupting at full rated current, Dielectric Voltage: Withstands 2,000V minimum, Mechanical :Terminal Accommodation #18-#12 AWG stranded copper wire only, Terminal Identification: Terminals identified in accordance with UL 498 and CSA, Environmental :Flammability: UL 94 HB or better, IP Suitability: IP20, Operating Temperatures: Maximum continuous 75°C, minimum -40°C (w/o impact)

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-20R
Industry Standard(s)	• CSA Certified to C22.2 No. 42 File 280C • NEMA® WD-6 Compliant • UL Listed to UL498 File E1706

Conductor

Number Of Conductors	3-Wire
Number Of Wires	3-Wire
Wire Size	#18 AWG to #12 AWG
Number Of Poles	2-Pole
Conductor Range	#18 AWG to #12 AWG

Current

Amperage Rating	20 A
Voltage Rating Description	125 V



Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125 VAC
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Display Size	Standard
Weight	0.15 lb.

General

Color	Black
Style	Standard
Cord Range	0.300"-0.660" (7.6-16.8)
Series	Valise®
Specifications	• Assembly Screws - Plated Steel • Assembly Screws - Plated steel • Cable Inserts - PPO • Contacts - Brass • Housing - Nylon • Terminal Clamp - Nickel plated steel • Terminal Screws - #8-32 Brass , multiple drive
UPC	783585019307
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	Valise
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	Max Continuous- 75 Degrees C, Minimum- -40 Without Impact
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Horsepower - Maximum1.00

Product Assets

- Catalog [English]
- Catalog Page [English]
- Installation Manual [Spanish, French, English]



A Hubbell brand