

HUBBELL
Wiring Device-Kellems

**Straight Blade Devices, Receptacles,
Commercial/Industrial Grade, 2-Pole 3-
Wire Grounding, 15A 250V, 6-15R, Brown,
Single Pack.**

By Hubbell Wiring Device-Kellems
Catalog # [HBL5656](#)

Straight Blade Devices, Receptacles, Commercial/Industrial
Grade, 2-Pole 3-Wire Grounding, 15A 250V, 6-15R, Brown, Single
Pack.



Features

- Stainless steel flange

Application

Heavy Duty

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-0, Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	6-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 • NEMA® WD-6 Compliant • UL Listed, File E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	250 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A

Voltage Rating	250 V
Wattage	3750 W
Connectivity	Side Wired Only
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.09 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	2.06 in
Width	1.47 in
Dimensions	1.09 in x 1.47 in x 2.06 in

General

Color	Brown
Series	Extra Heavy Duty
Specifications	• Face - Phenolic • Mounting Screw - Nickel plated brass • Power Contacts - .040" (1.0) Brass • Terminal Screw - #8-32 Brass, Multiple Drive
UPC	783585013206
Type	Flanged Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Flanged Single

Logistics

Pallet Quantity	4500
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1.5

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)

