

Straight Blade Devices, Receptacles, Panel Mount Single, Specification Grade, 2-Pole 3-Wire Grounding, 15A 250V, 6-15R, Brown, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [HBL5658](#)

Straight Blade Devices, Receptacles, Panel Mount Single, Specification Grade, 2-Pole 3-Wire Grounding, 15A 250V, 6-15R, Brown, Single Pack

Features

- Slender/compact design
- Triple wipe contacts
- Panel mount

Application

Extra Heavy Duty

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-O, Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	6-15R
Industry Standard(s)	• Certified to CSA 22.2, No. 42 File 285 • Guide RTRT Fed Spec WC596G • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current



Amperage Rating	15 A
Voltage Rating Description	250 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	250 V
Wattage	3750 W
Connectivity	Side Wired Only
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.75 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.47 in
Width	1.13 in
Dimensions	1.75 in x 1.13 in x 1.47 in

General

Color	Brown
Style	Panel Mount
Series	Extra Heavy Duty
Specifications	• Automatic Self-grounding Clip - Stainless steel • Body - PBT • Contacts - Brass • Insulator - RTP • Mounting Screws - Galvanized Steel • Mounting Strap - Galvanized steel • Terminal Screws - Brass
UPC	783585014388
Type	Single Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Single

Logistics

Pallet Quantity	4500
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	1.5

Product Assets

- Catalog [English]
- Catalog Page [English]



A Hubbell brand