HUBBELL
Wiring Device-Kellems

Watertight Devices, Twist-Lock® Receptacle with Lift Cover, 20A, 277VAC, 2 Pole, 3 Wire, Thermoplastic elastomer, NEMA L7-20R, Yellow.



By Hubbell Wiring Device-Kellems
Catalog # HBL67W49

WATERTIGHT RECEP ASSY,NEMA L7-20R

Features

- Impact resistant PBT lid, cover plate, and receptacle body
- Thermoplastic elastomer seal
- Stainless steel hardware and corrosion-resistant connection points

Performance

Electrical - Current Interrupting - Rated for current interruption per UL498, Electrical - Dielectric Voltage - 2500V AC, Electrical - Max Working Voltage - As marked, Electrical - Temperature Rise - 30°C max per UL498 at rated current, Environmental - UV resistance - All exposed materials are UV stabilized, Environmental - Moisture Resistance - UL Listed 4, 4X, 12, 6, 6P, Environmental - Operating Temperatures - -40°C (without impact) to +60°C continuous

Specifications

Standards - RoHS Compliance Status	CM
EU RoHS Indicator	Contact Manufacturer
Nema Rating	L7-20R
Industry Standard(s)	• IP69K In Use • Meets NEMA WD-1, WD-6 And ANSI Standards

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #8 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	277 VAC
Voltage Rating	277 VAC
Current / Amperage Rating	20 A

Dimensions

Length	4.56 in
Height	2.92 in
Width	3.10 in
Dimensions	4.56 in x 3.10 in x 2.92 in

General

Color	Yellow
UPC	783585433165
Type	Receptacle
Item Type	20A Watertight Twist-Lock® Receptacle

Logistics

Carton Quantity	5

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved