

Watertight Devices, Twist-Lock®
Receptacle with Lift Cover, 30A, 277V, 2
Pole, 3 Wire, Thermoplastic elastomer,
NEMA L7-30R, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL69W49](#)

WATERTIGHT RECEP ASSY,NEMA L7-30R

Features

- Impact resistant PBT lid, cover plate, and receptacle body
- Thermoplastic elastomer seal
- Stainless steel hardware and corrosion-resistant connection points

Performance

Electrical - Current Interrupting - Rated for current interruption per UL498, Electrical - Dielectric Voltage - 2500V AC, Electrical - Max Working Voltage - As marked, Electrical - Temperature Rise - 30°C max per UL498 at rated current, Environmental - UV resistance - All exposed materials are UV stabilized, Environmental - Moisture Resistance - UL Listed 4, 4X, 12, 6, 6P, Environmental - Operating Temperatures - -40°C (without impact) to +60°C continuous

Specifications

Nema Rating	L7-30R
Standards - RoHS Compliance	CM
Status	
Industry Standard(s)	• IP69K In Use • Meets NEMA WD-1, WD-6 And ANSI Standards
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire



Wire Size	#18 AWG to #8 AWG
-----------	-------------------

Current

Amperage Rating	30 A
Voltage Rating	277 VAC
Voltage Rating Description	277 VAC
Current / Amperage Rating	30 A

Dimensions

Height	2.92 in
Width	3.10 in
Length	4.56 in
Dimensions	4.56 in x 3.10 in x 2.92 in

General

Color	Yellow
UPC	783585433264
Type	Receptacle
Item Type	30A Watertight Twist-Lock® Receptacle

Logistics

Carton Quantity	5
-----------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)