

## Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 6) Receptacles, Metallic Body, 1050 Joules, 6' Cord

By Hubbell Wiring Device-Kellems  
Catalog # [HBL6MPS1050](#)



Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 6) Receptacles, Metallic Body, 1050 Joules, 6' Cord

### Features

- Office White color for aesthetics and metal housing
- 1050 joule rating
- 6 foot cord
- wire management

### Application

Standard Devices

### Performance

Electrical - Max Surge Current - 19.5kA, Electrical - Max. Operating Voltage - 130, Electrical - Operating Frequency - 50/60Hz, Environmental - Operating Temperature - -40°F to 160°F (-40°C to 70°C)

### Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes

### Conductor

Cord Length	6 ft
-------------	------

### Configuration

Number Of Outlets	6
-------------------	---

### Current

Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase
Current / Amperage Rating	15 A
Connectivity	Plug-In

### Dimensions

Display Size	1050 Joules
--------------	-------------

### General

Series	Economy Surge Strips
OEM Brand Name	Hubbell Wiring Device-Kellems
Outlet	Straight Blade 5-15R
Color	Office White
Item Type	Surge Protection Plug Strips
Material - Mounting Hardware	Portable
Type	Metallic
Material	Steel
Specifications	<ul style="list-style-type: none"> <li>• Color - Off. White</li> <li>• Height - 1.5" (38.1)</li> <li>• Housing - Metal</li> <li>• Length - 12.25" (311.2)</li> <li>• Width - 2.5" (63.5)</li> </ul>

UPC

783585120676

### Logistics

Carton Quantity	20
Pallet Quantity	400

### Operational

Response Time	5
Indicator(s) Type	LED Indicator
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)

### Product Assets

[Catalog \[English\]](#)  
[Catalog Page \[English\]](#)  
[Catalog Page \[English\]](#)  
[Installation Manual \[Spanish, French, English\]](#)