

Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 20A 250V, 2-Pole 2-Wire Non Grounding, L2-20R, Screw Terminal, Black and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL7101C](#)

Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 20A 250V, 2-Pole 2-Wire Non Grounding, L2-20R, Screw Terminal, Black and White

Features

- Insulated nylon construction to keep non-current carrying parts from becoming energized
- Tough ribbed nylon housing for secure gripping
- Two-part cord grip tightens with two screws for maximum retention force.

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #10 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L2-20P
Industry Standard(s)	Fed.Spec.W-C-596

Conductor

Number Of Wires	2-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole
Cable Range	0.230 - 0.720 in

Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A



Voltage Rating	250 VAC
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	20 A

Dimensions

Length	1.53 in
Display Size	Standard
Weight	0.15 lb.
Height	2.78 in
Width	1.53 in
Dimensions	1.53 in x 1.53 in x 2.78 in

General

Color	Black, White
Cord Range	0.220"-0.720"(5.6-18.3)
Specifications	• Assembly Screws - Steel - zinc plated • Body - Nylon • Contacts - Bronze • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screw - Brass
UPC	783585177007
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	20A Insulgrip® Connector
Material	Nylon

Logistics

Pallet Quantity	6000
Carton Quantity	10

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand