

Locking Devices, Twist-Lock®, Industrial, Male Plug, 20A 250V, 2-Pole 2-Wire Non-Grounding, L2-20P, Screw Terminal, Black and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL7102C](#)

Locking Devices, Twist-Lock®, Industrial, Male Plug, 20A 250V, 2-Pole 2-Wire Non-Grounding, L2-20P, Screw Terminal, Black and White

Features

- Integral dust shield protects wiring chamber from dust or contaminants.
- Self-threading screws specially designed for secure assembly
- Wiring chambers separate and positively insulate conductors and promote easy inspection

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L2-20P
Industry Standard(s)	• Certified to CSA C22.2 No.43 • Fed.Spec. W-C-597 • Listed to UL 499

Conductor

Number Of Wires	2-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole
Cable Range	0.220 - 0.720 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------



Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VAC
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	1.53 in
Display Size	Standard Sized
Weight	0.15 lb.
Height	1.97 in
Width	1.53 in
Dimensions	1.53 in x 1.53 in x 1.97 in

General

Color	Black, White
Cord Range	0.230"-0.720"(5.6-18.3)
Specifications	• Assembly Screws - Steel - zinc plated • Body - Nylon • Contacts - Bronze • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screw - Brass
UPC	783585177052
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	20A Male Non-Grounding Insulgrip® Plug
Material	Nylon

Logistics

Pallet Quantity	3600
Carton Quantity	10

Operational

Operating Temperature

Maximum continuous 75°C and
minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand