

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, Industrial,
Flush Receptacle, 20A 250V, 2-Pole 2-Wire
Non Grounding, L2-20R, Screw Terminal,
Black**

By Hubbell Wiring Device-Kellems
Catalog # [HBL7210B](#)

Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 20A
250V, 2-Pole 2-Wire Non Grounding, L2-20R, Screw Terminal,
Black



Features

- All-brass mounting and grounding system provides a lower resistance ground path and greater resistance to corrosion than steel mounting systems
- Face color coding by voltage facilitates locating and mating of proper devices
- High-impact, abuse-resistant nylon face
- Wire restraint recess for both back and side wiring, greatly reduces the possibility of loosening the terminal connection

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	L2-20R
Industry Standard(s)	Fed.Spec.W-C-596

Conductor

Number Of Wires	2-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC

Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VAC
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.20 lb.
Height	1.30 in
Width	1.40 in
Dimensions	3.28 in x 1.40 in x 1.30 in

General

Color	Black
Specifications	• Clamp - Brass • Contacts - Brass • Face - RTP • Ground Contact - Brass • Terminal Screws - Brass
UPC	783585237107
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	20A Single Flush Receptacle
Material	Thermoplastic

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	2

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Installation Manual [English]

